

# ArtiPress G Gloss



TYPICAL END USES	COLOUR PROFILE	FINISH	PRINTING METHODS
Catalogues Magazines Brochures	ECI_PSR_LWC_PLUS_V2.txt	Gloss	Rotogravure

## TECHNICAL DATASHEET (Target values)

Substance		g/m <sup>2</sup>	65	70	80	90
<b>Brightness</b>	D65/10°	%	89	90	91	91
<b>Whiteness</b>	CIE, ISO 11476, C2°	%	92	92	92	93
<b>L*</b>	D65/10°		93	93	93	93
<b>a*</b>	D65/10°		1.4	1.4	1.4	1.4
<b>b*</b>	D65/10°		-5.3	-5.3	-5.3	-5.3
<b>Opacity</b>	D65/10°	%	93	94	95	96
<b>Gloss Hunter</b>	ISO 8254-1	%	64	66	66	66
<b>Thickness</b>	ISO 534	µm	53	55	63	72
<b>Bulk</b>	ISO 534	cm <sup>3</sup> /g	0.82	0.79	0.79	0.80
<b>Smoothness</b>	ISO 8791-4 PPS 1MPa	µm	0.7	0.7	0.7	0.7

Technical specifications are target values and may be subject to production variations.

REEL SPECIFICATIONS	ENVIRONMENT	CERTIFICATES
Cores: 76 mm, 150 mm Trimmed width: 7200 mm Width: min. 388 mm, max. 4320 mm Diameters: min. 1000 mm, max 1300 mm Max. Weight: 10000 kg	Renewable fibre Recyclable paper Recyclable packaging materials Sustainable sources	EU Ecolabel ISO 9001 ISO 14001 ISO 50001 OHSAS 18001 FSC® CoC PEFC™ CoC

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19 °C and 23 °C.
- If the paper is stored in non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.

Kabel Premium Pulp & Paper GmbH  
Schwerter Straße 263  
58099 Hagen  
Tel +49 (0) 2331 699-0  
sales@k-premiumpaper.de